

Bremswelle Bildernummer 05016 - 0529



Lfd. Nr.	Bestell Nr.	Benennung	Abmessungen größter Durchmesser und Länge	Stück	Lieferant	Preis	Anmerkung ✓
508	B 12 042 A 02	Druckstange	d = 10 x 770	1			
509	000 991 04 40	Scheibe	13 x d = 26 x 1,75	2			
510	4 x 20 DIN 94	Splint	d = 4 x 20	2			
511	000 992 16 12	Rückholfeder	d = 12,5 x 75 x d = 1,8	1			
512	B 12 042 C 41	Führungsblech	30 x 4 x 105	1			
513	B8 / DIN 137	Federscheibe	B 8	2			
514	M 8 x 15 / DIN 558	Sechskantschraube	M 8 x 15	2			
515	000 991 30 34	Sechskantstift m, Hals	d = 10 x 30	1			
516	B 12 126 1032	Bremswelle vorn	d = 25 mm L = 262 mm	1			
517	000 990 19 50	Sekskantmutter	SW 11 x 6,5	4			
518	000 994 05 60	Sicherungsblech	23 x 57 x 0,625	2			
519	000 990 05 30	Sekskantschraube	SW 11 x 31	4			
520	B 12 120 1229	Zsb. Lenkbremspedal links		1			
521	B 12 120 1229	Zsb. Lenkbremspedal rechts		1			
522	A25/DIN 417	Seegersicherung	A25	1			
523	000 991 0540	Beilegescheibe	d = 26 x 34,5 t = 1	1			
524	000 990 0422	Beilegescheibe	d = 26 x 34,5 t = 0,5	1			
525	8,4 / DIN 433	Scheibe	d = 8,4	2			
526	2 x 15 / Din 94	Splint	2 x 15	2			
527	B 12 120 B 09	Zsb. Zugstange	d = 10 x 465	2			
528	8 x 40/DIN 1481	Spannstift	d = 8 mm L = 40 mm	1			
529	5 x 40/DIN 1481	Spannstift	d = 5 mm L = 40 mm	1			
...							
557	B 12 126 A 04	Hebelnabe (Lappen 6 ⁰ abgeb.)		1			
558	8 x 36 / DIN 1481	Spannstift	d = 8 x 36	1			
559	12 x 90 / DIN 1475	Zylinderkerbstift	d = 12 x 90	1			
...							
561	B 12 040 10 14	Zsb. Kupplungspedal		1			

